VISIBLE EMISSION OBSERVATION FORM

This form is designed to be used in conjunction with EPA Method 9, "Visual Determination of the Opacity of Emissions form Stationary Sources." Temporal changes in emission color, plume water droplet content, background color, sky conditions, observer position, etc. should be noted in the comments section adjacent to each minute of readings. Any information not dealt with elsewhere on the form should be noted under additional information. Following are brief descriptions of the type of information that needs to be entered on the form: for a more detailed discussion of each part of the form, refer to "Instructions for Use of Visible Emission Observation Form."

- Source Name: full company name, parent company or division or subsidiary information, if necessary.
- Address: street (not mailing or home office) address of facility where VE observation is being made.
 - Phone (Key Contact): number for appropriate contact.
 - Source ID Number: number from NEDS, agency file, etc.
- Process Equipment, Operating Mode: brief description of process equipment (include type of facility) and operating rate, % capacity, and/or mode (e.g. charging, tapping, shutdown).
- Control Equipment, Operating Mode: specify type of control device(s) and % utilization, control efficiency.
- Describe Emission Point: for identification purposes, stack or emission point appearance, location, and geometry; and whether emissions are confined (have a specifically designed outlet) or unconfined (fugitive).
- Height Above Ground Level: stack or emission point height relative to ground level; can use engineering drawings, Abney level, or clineometer.
- Height Relative to Observer: indicate height of emission point relative to the observation point.
- Distance from Observer: distance to emission point; can use rangefinder or map.
- Direction from Observer: direction plume is traveling from observer.
- Describe Emissions and Color: include physical characteristics, plume behavior (e.g., looping, lacy, condensing, fumigating, secondary particle formation, distance plume visible, etc.), and color of emissions (gray, brown, white, red, black, etc.). Note color changes in comments section.
- Visible Water Vapor Present?: check "yes" if visible water vapor is present.
- If Present, is Plume...: check "attached" if water droplet plume forms prior to exiting stack, and "detached" if water droplet plume forms after exiting stack.
- Point in Plume at Which Opacity was Determined: describe physical location in plume where readings were made (e.g., 1 ft above stack exit or 10 ft. after dissipation of water plume).
- Describe Plume Background: object plume is read against, include texture and atmospheric conditions (e.g., hazy).
- Background Color: sky blue, gray-white, new leaf green, etc.
 - Required by Reference 9; other items recommended.

- Sky Conditions: indicate cloud cover by percentage or by description (clear, scattered, broken, overcast).
- Wind Speed: record wind speed; can use Beaufort wind scale or hand-held anemometer to estimate.
- Wind Direction From: direction from which wind is blowing; can use compass to estimate to eight points.
- Ambient Temperature: in degrees Fahrenheit or Celsius.
 - Wet Bulb Temperature: can be measured using a sling psychrometer
 - RH Percent: relative humidity measured using a sling psychrometer; use local US Weather Bureau measurements only if nearby.
- Source Layout Sketch: include wind direction, sun position, associated stacks, roads, and other landmarks to fully identify location of emission point and observer position.
 - Draw North Arrow: to determine, point line of sight in direction of emission point, place compass beside circle, and draw in arrow parallel to compass needle.
 - Sun's Location: point line of sight in direction of emission point, move pen upright along sun location line, mark location of sun when pen's shadow crosses the observer's position.
- Observation Date: date observations conducted.
- Start Time, End Time: beginning and end times of observation period (e.g., 1635 or 4:35 p.m.).
- Data Set: percent opacity to nearest 5%; enter from left to right starting in left column. Use a second (third, etc.) form, if readings continue beyond 30 minutes. Use dash (-) for readings not made; explain in adjacent comments section.
 - Comments: note changing observation conditions, plume characteristics, and/or reasons for missed readings.
 - Range of Opacity: note highest and lowest opacity number.
- Observer's Name: print in full.
 - Observer's Signature, Date: sign and date after performing VE observation.
- Organization: observer's employer.
- Certified By, Date: name of "smoke school" certifying observer and date of most recent certification.

COLORADO DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT AIR POLLUTION CONTROL DIVISION - VISIBLE EMISSIONS OBSERVATION FORM Page No. Source Name Type of Source Observation Date Start Time End Time 15 30 0 45 Sec Comments Address Min City State Zip Phone # (Key Contact) Source ID Number Process Equipment Operating Mode Control Equipment Operating Mode 5 Describe Emission Point 6 Height above ground level Height relative to observer Inclinometer Reading Distance From Observer Direction From Observer 8 Start End Describe Emissions & Color 9 Visible Water Vapor Present? If yes, determine approximate distance from the No stack exit to where the plume was read 10 Point in Plume at Which Opacity Was Determined 11 Describe Plume Background Background Color 12 Start 13 Sky Conditions: Start 14 Wind Speed Wind Direction From 15 Wet Bulb Temp Ambient Temperature RH percent 16 NOTES: 17 1 Stack or Point Being Read 2 Wind Direction From 3 Observer Location 4 Sun Location 5 North Arrow 6 Other Stacks 18 19 20 21 22 23 24 25 26 27 28 29 30 Range of Opacity Minimum Maximum I have received a copy of these opacity observations Print Observer's Name Print Name: Observer's Signature Date Signature: Date Title Organization Certified By: Date